

APOLLO CLEAR GLOSS LACQUER

DESCRIPTION:

APOLLO CLEAR GLOSS LACQUER is a nitrocellulose-based coating used as finishing over lacquer sanding sealer. It is a general-purpose, high-quality clear gloss lacquer designed for fast and easy applications.

USE:

For wood furniture, panel boards, cabinets, wood trims and other woodcrafts.

APPEARANCE:

Glossy

APPLICATION:



Spray

RECOMMENDED THINNER:

Mayon Lacquer Thinner

RECOMMENDED MIXING RATIO:

1:1 (Paint: Thinner)

DRYING TIME:

Dry to touch: 5 minutes

Dry to sand / re-coat: allow 30 minutes

COVERAGE:

8 – 12 sq. m. per liter

PACKAGING:

1L and 3.75L rectangular can, 18L tin can;
200L drum

SHELF LIFE:

For Bottle: 1 year in unopened container
For Tin Can: 6 months in unopened container
For Drum: 3 months in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.



The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

LABEL ELEMENTS:



Danger: Highly flammable liquid and vapour. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. May cause damage to the central nervous system and the visual organs. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be harmful in contact with skin. May be harmful if inhaled. Harmful to aquatic life with long lasting effects.

Contains: Methylbenzene, Methanol, Naphtha (Petroleum), hydrotreated light, Di-(2-ethylhexyl)phthalate

Precaution: Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).



The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

