Technical Data Sheet



APOLLO DEAD FLAT LACQUER

DESCRIPTION:

APOLLO DEAD FLAT LACQUER is a nitrocellulose-based coating for interior application that exhibits a hard, durable & smooth matte finish. It is ideal to use Apollo Dead Flat Lacquer to ensure Longevity and to have a complete protection from Wood Deterioration.

PRIMARILY USED TO:

- Protect Wood from Decay and Deterioration.
- Enhance Wood Quality and provide a Smooth Matte Finish
- Lacquer Wood Products: Furniture, Doors, Cabinets, Panels, Fixtures, Fittings, Wrought Iron Furniture and etc.

APPEARANCE:

Cloudy Liquid

FINISH:

Flat

APPLICATION:



REDUCTION:

Mayon Lacquer Thinner

RECOMMENDED MIXING RATIO:

1:1 (Paint: Thinner)

DRYING TIME:

Dry to sand / re-coat: allow 20-30 minutes

COVERAGE:

8-12 sq. m. / Liter

PACKAGING:

350cc bottle; 3.75L rectangular can; 200L drum

SHELF LIFE:

For Bottle: 1 year in unopened container
For Rectangular Can: 6 months in unopened container
For Drum: 3 months in unopened container

STORAGE AND DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.



The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



No. 2, 3rd Avenue, S.Osmeña Blvd., North Reclamation Area, Cebu City, 6000, Philippines www.islandpaints.com info@treasureisland.com.ph **Tel # Head Office :** 232-0513 to 17 **Fax:**

(63-32) 232-0518

Information Office: 83-35 Plaridel St., Cebu City, 6000, Philippines Tel # for Info Office: 254-2226

412-4113 412-4082

Fax: (63-32) 255-2656

Technical Data Sheet Significant Sheet Premium QUALITY Premium QUALITY

LABEL ELEMENTS:



Danger: Highly flammable liquid and vapour. May cause allergy, asthma symptoms, or breathing difficulties if inhaled. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to the central nervous system and the visual organs. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Causes skin and serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. May be harmful if inhaled. Harmful to aquatic life with long lasting effects.

Contains: Methanol, Methylbenzene, Naphtha (petroleum), hydrotreated light, Modified Rosin Ester

Precaution: Avoid exposure — obtain special instructions before use. Keep locked up and out of the reach of children. Do not breathe gas/fumes/vapour/spray. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing, gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). In case of accident by inhalation: remove casualty to fresh air and keep at rest.



The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



(63-32) 232-0518