Technical Data Sheet



GI PAINT AND VARNISH REMOVER

DESCRIPTION:

GI PAINT AND VARNISH REMOVER is a Methylene Chloride-based paint and varnish remover. Upon application, the paint or varnish film starts to bubble, wrinkle, softens and detach from the surface. It comes in thick fluid and conveniently applied even on vertical and upright surfaces. Ideally used as a preparation when making a renovation or a restoration.

PRIMARILY USED TO:

- Stripping layers of Paint in Wood, Concrete and Metal Surfaces
- Removing Varnish in Wood Surfaces.
- Cleaning Paint and Varnish spill and spots.

CAN ALSO BE USED TO:

Remove Adhesives

COLOR:

Clear

COVERAGE:

Approximately 8-10 sq. m. / gal, depending on the type of paint / varnish to be removed.

APPLICATION:



Allow 5 – 15 minutes reaction time after application. When necessary, scratch the old coating with a knife after application to enhance softening and penetration. With the aid of a scraper or putty knife, the softened film will easily be removed.

PACKAGING:

350cc bottle, 3.75L rectangular can

SHELF LIFE:

6 months in unopened container

STORAGE AND DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.



The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



No. 2, 3rd Avenue, S.Osmeña Blvd., North Reclamation Area, Cebu City, 6000, Philippines www.islandpaints.com

Technical Data Sheet Significant of the second of the sec

LABEL ELEMENTS:







Danger: Highly flammable liquid and vapour. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to the central nervous system and the visual organs. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Harmful if inhaled. Causes skin irritation. May be harmful if swallowed.

Contains: Methanol, Dichloromethane, Methylbenzene

Precaution: Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). In case of accident by inhalation: remove casualty to fresh air and keep at rest



The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



Head Office Address:

No. 2, 3rd Avenue, S.Osmeña Blvd., North Reclamation Area, Cebu City, 6000, Philippines www.islandpaints.com info@treasureisland.com.ph Tel # Head Office : 232-0513 to 17

Fax: (63-32) 232-0518

Information Office: 83-35 Plaridel St., Cebu City, 6000, Philippines

Tel # for Info Office: 254-2226

254-2226 412-4113 412-4082 Fax:

(63-32) 255-2656