

Safety Data Sheet according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

1 Identification

- **Product identifier**
- **Trade name:** GI PLASTIC VARNISH
- **Article number:** CWCCOV-00031
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Treasure Island Industrial Corp.
No.2, 3rd Ave. S. Osmena Blvd.
North Reclamation Area
Cebu City 6000
PHILIPPINES
doo@treasureisland.com.ph
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**



Flam. Liq. 2	H225	Highly flammable liquid and vapour.
--------------	------	-------------------------------------



Muta. 1B	H340	May cause genetic defects.
Carc. 1A	H350	May cause cancer.
Repr. 1B	H360	May damage fertility or the unborn child.



Eye Dam. 1	H318	Causes serious eye damage.
------------	------	----------------------------



Skin Irrit. 2	H315	Causes skin irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Acute Tox. 5	H333	May be harmful if inhaled.
Aquatic Acute 3	H402	Harmful to aquatic life.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

CWCCOV-00031

(Contd. on page 2)

Safety Data Sheet according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: **GI PLASTIC VARNISH**

(Contd. of page 1)

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



T; Toxic

R45-46-60-61: *May cause cancer. May cause heritable genetic damage. May impair fertility. May cause harm to the unborn child.*



Xn; Harmful

R21: *Harmful in contact with skin.*



Xi; Irritant

R37/38-41: *Irritating to respiratory system and skin. Risk of serious damage to eyes.*



Xi; Sensitising

R43: *May cause sensitisation by skin contact.*



F; Highly flammable

R11: *Highly flammable.*

R67: *Vapours may cause drowsiness and dizziness.*

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



T Toxic

F Highly flammable

· **Hazard-determining components of labelling:**

Poly(melamine-co-formaldehyde), isobutylated Naphtha (petroleum), hydrotreated light di-(2-ethylhexyl) phthalate

· **Risk phrases:**

- 45 *May cause cancer.*
- 46 *May cause heritable genetic damage.*
- 60 *May impair fertility.*
- 61 *May cause harm to the unborn child.*
- 11 *Highly flammable.*
- 21 *Also harmful in contact with skin.*
- 37/38 *Irritating to respiratory system and skin.*
- 41 *Risk of serious damage to eyes.*
- 43 *May cause sensitisation by skin contact.*
- 67 *Vapours may cause drowsiness and dizziness.*

(Contd. on page 3)

Safety Data Sheet

according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 2)

Safety phrases:

- 53 Avoid exposure - obtain special instructions before use.
- 1/2 Keep locked up and out of the reach of children.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).













Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition / information on ingredients

Chemical characterisation: Mixtures
Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 68002-21-1	Poly(melamine-co-formaldehyde), isobutylated  T Carc. Cat. 1, Muta. Cat. 3 R45-46  Xi R37/38-41  Xi R43 R10-67 <hr style="border-top: 1px dashed #000;"/>  Flam. Liq. 3, H226  Muta. 2, H341; Carc. 1A, H350  Eye Dam. 1, H318  Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335-H336	
CAS: 78-83-1	butyl alcohol (except tert-butyl alcohol)  Xi R37/38-41 R10-67 <hr style="border-top: 1px dashed #000;"/>  Flam. Liq. 3, H226  Eye Dam. 1, H318  Skin Irrit. 2, H315; STOT SE 3, H335-H336 Acute Tox. 5, H303; Acute Tox. 5, H313	
CAS: 64742-16-1	Petroleum Resin  Xn R21/22 R53 <hr style="border-top: 1px dashed #000;"/> Acute Tox. 5, H303; Acute Tox. 5, H313; Aquatic Chronic 4, H413	

(Contd. on page 4)

PH

Safety Data Sheet































according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 3)

CAS: 108-88-3	Methylbenzene  <i>Xn R48/20-63-65</i>  <i>Xi R38</i>  <i>F R11</i> <i>R67</i> <i>Repr. Cat. 3</i> <hr style="border-top: 1px dashed #000;"/>  <i>Flam. Liq. 2, H225</i>  <i>Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304</i>  <i>Skin Irrit. 2, H315; STOT SE 3, H336</i>  <i>Acute Tox. 5, H303</i>	
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light  <i>T Carc. Cat. 2, Muta. Cat. 2 R45-46</i>  <i>Xn R65</i> <hr style="border-top: 1px dashed #000;"/>  <i>Flam. Liq. 2, H225</i>  <i>Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304</i>  <i>Aquatic Chronic 2, H411</i>  <i>Skin Irrit. 2, H315; STOT SE 3, H336</i> <i>Aquatic Acute 2, H401</i>	
CAS: 67-56-1	Methanol  <i>T R23/24/25-39/23/24/25</i>  <i>F R11</i> <hr style="border-top: 1px dashed #000;"/>  <i>Flam. Liq. 2, H225</i>  <i>Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331</i>  <i>STOT SE 1, H370</i> <i>Specific concentration limits: STOT SE 1; H370: C ≥ 10 %</i> <i>STOT SE 2; H371: 3 % ≤ C < 10 %</i>	
CAS: 1330-20-7	Dimethylbenzene  <i>Xn R20/21</i>  <i>Xi R38</i> <i>R10</i> <hr style="border-top: 1px dashed #000;"/>  <i>Flam. Liq. 3, H226</i>  <i>Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315</i> <i>Acute Tox. 5, H303</i>	
CAS: 117-81-7	di-(2-ethylhexyl) phthalate  <i>T Repr. Cat. 2 R60-61</i>  <i>Repr. 1B, H360</i>	
CAS: 123-86-4	Butyl Ethanoate  <i>Xn R22</i>  <i>Xi R36/38</i>  <i>F+ R12</i> <i>R67</i> <hr style="border-top: 1px dashed #000;"/>  <i>Flam. Liq. 3, H226</i>  <i>Acute Tox. 3, H301</i>  <i>Skin Irrit. 2, H315; Eye Irritation 2A, H319; STOT SE 3, H336</i>	

· SVHC

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

PH

(Contd. on page 5)

Safety Data Sheet according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 4)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
*Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.*
- **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*
- **After eye contact:** *Rinse opened eye for several minutes under running water. Then consult a doctor.*
- **After swallowing:** *If symptoms persist consult doctor.*
- **Information for doctor:**
Most important symptoms and effects, both acute and delayed No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** *CO₂, sand, extinguishing powder. Do not use water.*
- **For safety reasons unsuitable extinguishing agents:** *Water with full jet*
- **Special hazards arising from the substance or mixture** *No further relevant information available.*
- **Advice for firefighters**
- **Protective equipment:** *No special measures required.*

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
*Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents*
- **Reference to other sections**
*See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.*

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
*Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.*

(Contd. on page 6)

PH

Safety Data Sheet according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 5)

- **Information about fire - and explosion protection:**
 Keep ignition sources away - Do not smoke.
 Protect from heat.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
 Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

Ingredients with limit values that require monitoring at the workplace:
CAS: 78-83-1 butyl alcohol (except tert-butyl alcohol)

PEL (USA)	Long-term value: 300 mg/m ³ , 100 ppm
REL (USA)	Long-term value: 150 mg/m ³ , 50 ppm
TLV (USA)	Long-term value: 50 ppm

CAS: 108-88-3 Methylbenzene

PEL (USA)	Long-term value: 200 ppm Ceiling limit: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, OTO, A4

CAS: 67-56-1 Methanol

PEL (USA)	Long-term value: 260 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV (USA)	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI

CAS: 1330-20-7 Dimethylbenzene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

(Contd. on page 7)

Safety Data Sheet according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 6)

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

PEL (USA)	Long-term value: 5 mg/m ³
REL (USA)	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³ See Pocket Guide App. A
TLV (USA)	Long-term value: (5) mg/m ³ , NIC-0.03 ppm NIC-Skin, A3

CAS: 123-86-4 Butyl Ethanoate

PEL (USA)	Long-term value: 710 mg/m ³ , 150 ppm
REL (USA)	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV (USA)	Short-term value: 150 ppm Long-term value: 50 ppm

Ingredients with biological limit values:
CAS: 108-88-3 Methylbenzene

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

CAS: 67-56-1 Methanol

BEI (USA)	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----------	---

CAS: 1330-20-7 Dimethylbenzene

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

(Contd. on page 8)

PH

Safety Data Sheet according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 7)

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	108 °C

· **Flash point:** < 0 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 215 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 9)

Safety Data Sheet according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 8)

· Explosion limits:	
Lower:	1.2 Vol %
Upper:	44 Vol %
· Vapour pressure at 20 °C:	128 hPa
· Density at 20 °C:	0.86 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	35.4 %
VOC (EC)	35.37 %
Solids content:	28.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· LD/LC50 values relevant for classification:

CAS: 78-83-1 butyl alcohol (except tert-butyl alcohol)

Oral	LD50	2,460 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)

CAS: 108-88-3 Methylbenzene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

CAS: 67-56-1 Methanol

Oral	LD50	5,628 mg/kg (rat)
------	------	-------------------

(Contd. on page 10)

Safety Data Sheet according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 9)

Dermal	LD50	15,800 mg/kg (rabbit)
CAS: 1330-20-7 Dimethylbenzene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
CAS: 117-81-7 di-(2-ethylhexyl) phthalate		
Oral	LD50	30,600 mg/kg (rat)
Dermal	LD50	25,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Strong irritant with the danger of severe eye injury.
- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.
- **Additional toxicological information:**
 The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
 Harmful
 Irritant
 Carcinogenic.
 The product can cause inheritable damage.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

 PH
 (Contd. on page 11)

Safety Data Sheet according to GHS


Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 10)

14 Transport information

· UN-Number · ADR, IMDG, IATA	UN1263
· UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
· Transport hazard class(es) · ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADR, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number:	Warning: Flammable liquids. 33 F-E, <u>S-E</u>
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

 · **Safety, health and environmental regulations/legislation specific for the substance or mixture**

 · **Philippines Inventory of Chemicals and Chemical Substances**

CAS: 68002-21-1	Poly(melamine-co-formaldehyde), isobutylated
CAS: 78-83-1	butyl alcohol (except tert-butyl alcohol)
CAS: 64742-16-1	Petroleum Resin
CAS: 108-88-3	Methylbenzene

(Contd. on page 12)

Safety Data Sheet

according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 11)

CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light
CAS: 67-56-1	Methanol
CAS: 1330-20-7	Dimethylbenzene
CAS: 117-81-7	di-(2-ethylhexyl) phthalate
CAS: 67-63-0	Isopropyl Alcohol
CAS: 111-76-2	Normal Butyl Cellusolve
CAS: 78-93-3	Methyl ethyl ketone
CAS: 67-64-1	propanone
CAS: 123-86-4	Butyl Ethanoate

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

- **National regulations:**

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Other regulations, limitations and prohibitive regulations**

- **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 117-81-7	di-(2-ethylhexyl) phthalate
---------------	-----------------------------

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H360	May damage fertility or the unborn child.

(Contd. on page 13)

Safety Data Sheet according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 12)

- H361 Suspected of damaging fertility or the unborn child.
 H370 Causes damage to organs.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H401 Toxic to aquatic life.
 H411 Toxic to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.
- R10 Flammable.
 R11 Highly flammable.
 R12 Extremely flammable.
 R20/21 Harmful by inhalation and in contact with skin.
 R21/22 Harmful in contact with skin and if swallowed.
 R22 Harmful if swallowed.
 R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
 R36/38 Irritating to eyes and skin.
 R37/38 Irritating to respiratory system and skin.
 R38 Irritating to skin.
 R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
- R41 Risk of serious damage to eyes.
 R43 May cause sensitisation by skin contact.
 R45 May cause cancer.
 R46 May cause heritable genetic damage.
 R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 R53 May cause long-term adverse effects in the aquatic environment.
 R60 May impair fertility.
 R61 May cause harm to the unborn child.
 R63 Possible risk of harm to the unborn child.
 R65 Harmful: may cause lung damage if swallowed.
 R67 Vapours may cause drowsiness and dizziness.

 · **Department issuing SDS:** Product safety department

 · **Contact:** Mr. Ong

 · **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 3: Acute toxicity – Category 3
 Acute Tox. 5: Acute toxicity – Category 5
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
 Skin Sens. 1: Skin sensitisation – Category 1
 Muta. 1B: Germ cell mutagenicity – Category 1B
 Muta. 2: Germ cell mutagenicity – Category 2
 Carc. 1A: Carcinogenicity – Category 1A
 Carc. 1B: Carcinogenicity – Category 1B
 Repr. 1B: Reproductive toxicity – Category 1B

(Contd. on page 14)

Safety Data Sheet
according to GHS

Printing date 24.11.2022

Revision: 22.11.2022

Trade name: GI PLASTIC VARNISH

(Contd. of page 13)

Repr. 2: Reproductive toxicity – Category 2
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4
· *** Data compared to the previous version altered.**

PH