



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

1 Identification

- **Product identifier**
- **Trade name:** APOLLO LACQUER SANDING SEALER
- **Article number:** CWCNCL-00009
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Company Name : Treasure Island Chemical Corp.
Company Address: Sitio Pilit Cabancalan, 6014 City of Mandaue, Cebu Philippines
Email Address: ddo@treasureisland.com.ph
Contact No.: +63 32 346 49 54-55
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**



GHS02 flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 1B

H340 May cause genetic defects.

Carc. 1B

H350 May cause cancer.

Repr. 1B

H360 May damage fertility or the unborn child.

STOT SE 1

H370 Causes damage to the central nervous system and the visual organs.

STOT RE 2

H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1

H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4

H302 Harmful if swallowed.

Acute Tox. 4

H332 Harmful if inhaled.

Skin Irrit. 2

H315 Causes skin irritation.

Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

(Contd. on page 2)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 1)

STOT SE 3

H336 May cause drowsiness or dizziness.

Acute Tox. 5

H313 May be harmful in contact with skin.

Aquatic Acute 3

H402 Harmful to aquatic life.

Aquatic Chronic 3

H412 Harmful to aquatic life with long lasting effects.

CWCNCV-00009

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



T; Toxic

R45-46-60-61-39/23/24/25: May cause cancer. May cause heritable genetic damage. May impair fertility. May cause harm to the unborn child. Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.



Xn; Harmful

R20/21/22-48/20-65: Harmful by inhalation, in contact with skin and if swallowed. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Harmful: may cause lung damage if swallowed.



Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.



Xi; Irritant

R36/38: Irritating to eyes and skin.



F; Highly flammable

R11: Highly flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:



T Toxic
F Highly flammable

Hazard-determining components of labelling:

Methanol

Methylbenzene

Naphtha (petroleum), hydrotreated light

(Contd. on page 3)



Safety Data Sheet according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 2)

MODIFIED ROSIN ESTER

· **Risk phrases:**

- 45 May cause cancer.
- 46 May cause heritable genetic damage.
- 60 May impair fertility.
- 61 May cause harm to the unborn child.
- 11 Highly flammable.
- 20/21/22 Also harmful by inhalation, in contact with skin and if swallowed.
- 36/38 Irritating to eyes and skin.
- 39/23/24/25 Also toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
- 42/43 May cause sensitisation by inhalation and skin contact.
- 48/20 Also harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 65 Harmful: may cause lung damage if swallowed.

· **Safety phrases:**

- 53 Avoid exposure - obtain special instructions before use.
- 1/2 Keep locked up and out of the reach of children.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 63 In case of accident by inhalation: remove casualty to fresh air and keep at rest.

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition / information on ingredients

· **Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 4)

PH



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 3)

Dangerous components:

CAS: 108-88-3	<p>Methylbenzene</p> <p> Xn R48/20-63-65</p> <p> Xi R38</p> <p> F R11</p> <p>R67</p> <p>Repr. Cat. 3</p> <p> Flam. Liq. 2, H225</p> <p> Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304</p> <p> Skin Irrit. 2, H315; STOT SE 3, H336</p> <p> Acute Tox. 5, H303</p>	
CAS: 64742-49-0	<p>Naphtha (petroleum), hydrotreated light</p> <p> T Carc. Cat. 2, Muta. Cat. 2 R45-46</p> <p> Xn R65</p> <p> Flam. Liq. 2, H225</p> <p> Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304</p> <p> Aquatic Chronic 2, H411</p> <p> Skin Irrit. 2, H315; STOT SE 3, H336</p> <p>Aquatic Acute 2, H401</p>	
CAS: 67-56-1	<p>Methanol</p> <p> T R23/24/25-39/23/24/25</p> <p> F R11</p> <p> Flam. Liq. 2, H225</p> <p> Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331</p> <p> STOT SE 1, H370</p> <p>Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %</p>	
CAS: 68083-19-2	<p>MODIFIED ROSIN ESTER</p> <p> Xn R20/21/22</p> <p> Xn R42/43</p> <p> Resp. Sens. 1B, H334</p> <p> Skin Sens. 1B, H317</p> <p>Acute Tox. 5, H303; Acute Tox. 5, H313; Acute Tox. 5, H333</p>	
CAS: 123-86-4	<p>Butyl Ethanoate</p> <p> Xn R22</p> <p> Xi R36/38</p> <p> F+ R12</p> <p>R67</p> <p> Flam. Liq. 3, H226</p> <p> Acute Tox. 3, H301</p> <p> Skin Irrit. 2, H315; Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H336</p>	
CAS: 111-76-2	<p>BUTYL CELLOSOLVE</p> <p> Xn R20/21/22</p> <p> Xi R36/38</p> <p> Flam. Liq. 3, H226</p> <p> Acute Tox. 3, H331</p> <p> Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319</p>	

(Contd. on page 5)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 4)

CAS: 141-78-6	ETHYL ACETATE Xi R36 F R11 R66-67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 78-93-3	Methyl Ethyl Ketone Xi R36 F R11 R66-67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H303; Acute Tox. 5, H313	
CAS: 67-63-0	Isopropyl Alcohol Xi R36 F R11 R67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H333	
CAS: 1330-20-7	Dimethylbenzene Xn R20/21 Xi R38 R10 Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 Acute Tox. 5, H303	
CAS: 557-05-1	ZINC STEARATE	
	cellulose nitrate F R11 Flam. Sol. 1, H228	
CAS: 117-81-7	di-(2-ethylhexyl) phthalate T Repr. Cat. 2 R60-61 Repr. 1B, H360	

· SVHC

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 6)



Safety Data Sheet according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 5)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Call for a doctor immediately.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

(Contd. on page 7)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 6)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 108-88-3 Methylbenzene

PEL (USA) Long-term value: 200 ppm
Ceiling limit: 300; 500* ppm
*10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm
BEI, OTO, A4

CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light

TLV (USA) Long-term value: 100 ppm
Skin, A3

CAS: 67-56-1 Methanol

PEL (USA) Long-term value: 260 mg/m³, 200 ppm

REL (USA) Short-term value: 325 mg/m³, 250 ppm
Long-term value: 260 mg/m³, 200 ppm
Skin

TLV (USA) Short-term value: 328 mg/m³, 250 ppm
Long-term value: 262 mg/m³, 200 ppm
Skin; BEI

CAS: 123-86-4 Butyl Ethanoate

PEL (USA) Long-term value: 710 mg/m³, 150 ppm

REL (USA) Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm

TLV (USA) Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

CAS: 111-76-2 BUTYL CELLOSOLVE

PEL (USA) Long-term value: 240 mg/m³, 50 ppm
Skin

(Contd. on page 8)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 7)

REL (USA)	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV (USA)	Long-term value: 97 mg/m ³ , 20 ppm BEI, A3
CAS: 141-78-6 ETHYL ACETATE	
PEL (USA)	Long-term value: 1400 mg/m ³ , 400 ppm
REL (USA)	Long-term value: 1400 mg/m ³ , 400 ppm
TLV (USA)	Long-term value: 1440 mg/m ³ , 400 ppm
CAS: 78-93-3 Methyl Ethyl Ketone	
PEL (USA)	Long-term value: 590 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV (USA)	Short-term value: 150 ppm Long-term value: 75 ppm BEI, Skin
CAS: 67-63-0 Isopropyl Alcohol	
PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 491 mg/m ³ , 200 ppm BEI, A4
CAS: 1330-20-7 Dimethylbenzene	
PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, A4
CAS: 557-05-1 ZINC STEARATE	
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 10* 3** mg/m ³ *inhalable, **respirable particulate matter, *A4
CAS: 117-81-7 di-(2-ethylhexyl) phthalate	
PEL (USA)	Long-term value: 5 mg/m ³
REL (USA)	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³ See Pocket Guide App. A
TLV (USA)	Long-term value: 0.1 mg/m ³ Skin, A3

(Contd. on page 9)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 8)

Ingredients with biological limit values:

CAS: 108-88-3 Methylbenzene

<i>BEI (USA)</i>	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

CAS: 67-56-1 Methanol

<i>BEI (USA)</i>	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
------------------	---

CAS: 111-76-2 BUTYL CELLOSOLVE

<i>BEI (USA)</i>	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
------------------	--

CAS: 78-93-3 Methyl Ethyl Ketone

<i>BEI (USA)</i>	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)
------------------	---

CAS: 67-63-0 Isopropyl Alcohol

<i>BEI (USA)</i>	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
------------------	---

CAS: 1330-20-7 Dimethylbenzene

<i>BEI (USA)</i>	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
------------------	--

(Contd. on page 10)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 9)

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

<p>BEI (USA)</p>	<p>5 µg/g creatinine Medium: - Time: Postshift Parameter: MEHP (population-based)</p> <p>20 µg/g creatinine Medium: - Time: Postshift Parameter: MEHHP (population-based)</p> <p>15 µg/g creatinine Medium: - Time: Postshift Parameter: MEOHP (population-based)</p> <p>25 µg/g creatinine Medium: - Time: Postshift Parameter: MECPP (population-based)</p>
-------------------------	---

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 11)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 10)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	64.7 °C

· **Flash point:** < 0 °C

· **Flammability:** Highly flammable.

· **Auto-ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· Lower:	1.2 Vol %
· Upper:	12 Vol %

· **Vapour pressure at 20 °C:** 105 hPa

· Density at 20 °C:	0.89 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

(Contd. on page 12)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 11)

· Solvent content:	
Organic solvents:	79.4 %
VOC (EC)	79.38 %
Solids content:	
	22.3 %
· Other information	
	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

CAS: 108-88-3 Methylbenzene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

CAS: 67-56-1 Methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

CAS: 111-76-2 BUTYL CELLOSOLVE

Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

CAS: 78-93-3 Methyl Ethyl Ketone

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)

CAS: 67-63-0 Isopropyl Alcohol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

(Contd. on page 13)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 12)

CAS: 1330-20-7 Dimethylbenzene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
CAS: 117-81-7 di-(2-ethylhexyl) phthalate		
Oral	LD50	30,600 mg/kg (rat)
Dermal	LD50	25,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation**
Sensitisation possible through inhalation.
Sensitisation possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant
Carcinogenic.
The product can cause inheritable damage.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 14)



Safety Data Sheet
according to GHS

Printing date 18.02.2026


Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 13)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · ADR, IMDG, IATA	UNI263
· UN proper shipping name · ADR · IMDG, IATA	1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
· Transport hazard class(es) · ADR, IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	Yes
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number:	Warning: Flammable liquids. 33 F-E, <u>S-E</u>
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 15)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 14)

· **UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**

CAS: 108-88-3	Methylbenzene
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light
CAS: 67-56-1	Methanol
CAS: 68083-19-2	MODIFIED ROSIN ESTER
CAS: 123-86-4	Butyl Ethanoate
CAS: 111-76-2	BUTYL CELLOSOLVE
CAS: 141-78-6	ETHYL ACETATE
CAS: 78-93-3	Methyl Ethyl Ketone
CAS: 67-63-0	Isopropyl Alcohol
CAS: 63148-69-6	ALKYD RESIN
CAS: 1330-20-7	Dimethylbenzene
CAS: 557-05-1	ZINC STEARATE
CAS: 117-81-7	di-(2-ethylhexyl) phthalate
CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
CAS: 471-34-1	Calcium Carbonate
CAS: 14807-96-6	Hydrated Magnesium Silicate
CAS: 95-63-6	1,2,4-trimethylbenzene
CAS: 85535-84-8	alkanes, C10-13, chloro
CAS: 1317-65-3	Calcium Carbonate
CAS: 1318-93-0	Montmorillonite
CAS: 112926-00-8	Precipitated silica (Silica-Amorphous)
CAS: 21645-51-2	aluminium hydroxide
CAS: 108-67-8	1,3,5-trimethylbenzene
CAS: 556-67-2	octamethylcyclotetrasiloxane
CAS: 63449-39-8	Paraffin waxes and Hydrocarbon waxes, chloro
CAS: 98-82-8	isopropylbenzene
CAS: 64742-88-7	Solvent naphtha (petroleum), medium aliph.
CAS: 100-41-4	ethylbenzene
CAS: 14808-60-7	Silicon Dioxide
CAS: 108-93-0	cyclohexanol

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

(Contd. on page 16)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 15)

· **Seveso category**

H3 STOT SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t**

· **Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t**

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 117-81-7	di-(2-ethylhexyl) phthalate
---------------	-----------------------------

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H333 May be harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H336 May cause drowsiness or dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H371 May cause damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

R10 Flammable.

(Contd. on page 17)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 16)

- R11 *Highly flammable.*
- R12 *Extremely flammable.*
- R20/21 *Harmful by inhalation and in contact with skin.*
- R20/21/22 *Harmful by inhalation, in contact with skin and if swallowed.*
- R22 *Harmful if swallowed.*
- R23/24/25 *Toxic by inhalation, in contact with skin and if swallowed.*
- R36 *Irritating to eyes.*
- R36/38 *Irritating to eyes and skin.*
- R38 *Irritating to skin.*
- R39/23/24/25 *Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.*
- R42/43 *May cause sensitisation by inhalation and skin contact.*
- R45 *May cause cancer.*
- R46 *May cause heritable genetic damage.*
- R48/20 *Harmful: danger of serious damage to health by prolonged exposure through inhalation.*
- R60 *May impair fertility.*
- R61 *May cause harm to the unborn child.*
- R63 *Possible risk of harm to the unborn child.*
- R65 *Harmful: may cause lung damage if swallowed.*
- R66 *Repeated exposure may cause skin dryness or cracking.*
- R67 *Vapours may cause drowsiness and dizziness.*

· **Department issuing SDS:** Product safety department

· **Contact:** Mr. Ong

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Sol. 1: Flammable solids – Category 1

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 5: Acute toxicity – Category 5

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Resp. Sens. 1B: Respiratory sensitisation – Category 1B

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Muta. 1B: Germ cell mutagenicity – Category 1B

(Contd. on page 18)



Safety Data Sheet
according to GHS

Printing date 18.02.2026

Revision: 18.02.2026

Trade name: APOLLO LACQUER SANDING SEALER

(Contd. of page 17)

Carc. 1B: Carcinogenicity – Category 1B
Repr. 1B: Reproductive toxicity – Category 1B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
*** Data compared to the previous version altered.**

PH