



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

1 Identification


- **Product identifier**
- **Trade name: GI PAINT AND VARNISH REMOVER**
- **Article number: CWCCHO-00026**
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Company Name : Treasure Island Chemical Corp.
Company Address: Sitio Pilit Cabancalan, 6014 City of Mandaue, Cebu Philippines
Email Address: ddo@treasureisland.com.ph
Contact No.: +63 32 346 49 54-55
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**



Flam. Liq. 2 H225 Highly flammable liquid and vapour.




- Carc. 1B H350 May cause cancer.
- Repr. 2 H361 Suspected of damaging fertility or the unborn child.
- STOT SE 1 H370 Causes damage to the central nervous system and the visual organs.
- STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
- Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



- Acute Tox. 4 H332 Harmful if inhaled.
 - Skin Irrit. 2 H315 Causes skin irritation.
 - Acute Tox. 5 H303 May be harmful if swallowed.
- CWCCHO-00025

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

(Contd. on page 2)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

(Contd. of page 1)



Xn; Harmful

R20/21/22-40: Harmful by inhalation, in contact with skin and if swallowed. Limited evidence of a carcinogenic effect.



F; Highly flammable

R11: Highly flammable.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



T Toxic

F Highly flammable

· **Hazard-determining components of labelling:**

Methanol

Methylene chloride

· **Risk phrases:**

11 Highly flammable.

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

40 Limited evidence of a carcinogenic effect.

· **Safety phrases:**

1/2 Keep locked up and out of the reach of children.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

PH

(Contd. on page 3)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

(Contd. of page 2)

3 Composition / information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 75-09-2	Methylene chloride Xn R40 Carc. Cat. 3 Carc. 2, H351 Acute Tox. 4, H302 Acute Tox. 5, H333	
CAS: 67-56-1	Methanol T R23/24/25-39/23/24/25 F R11 Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %	
CAS: 1330-20-7	Dimethylbenzene Xn R20/21 Xi R38 R10 Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 Acute Tox. 5, H303	
CAS: 67-63-0	Isopropyl Alcohol Xi R36 F R11 R67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H333	
CAS: 127087-87-0	α-(4-nonylphenyl)-ω-hydroxy poly(oxy-1,2-ethanediyl), branched Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 7664-41-7	Ammonia T R23 C R34 N R50 R10 Press. Gas C, H280 Acute Tox. 3, H331 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Acute Tox. 4, H302 Flam. Gas 2, H221	

(Contd. on page 4)



Safety Data Sheet according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

(Contd. of page 3)

· **SVHC**

CAS: 127087-87-0 α -(4-nonylphenyl)- ω -hydroxy poly(oxy-1,2-ethanediyl), branched

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Call for a doctor immediately.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

See Section 13 for disposal information.

(Contd. of page 4)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **Control parameters**

Ingredients with limit values that require monitoring at the workplace:

CAS: 75-09-2 Methylene chloride

PEL (USA)	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 174 mg/m ³ , 50 ppm BEI, A3

CAS: 67-56-1 Methanol

PEL (USA)	Long-term value: 260 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV (USA)	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

CAS: 1330-20-7 Dimethylbenzene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
-----------	--

(Contd. on page 6)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

(Contd. of page 5)

REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, A4

CAS: 67-63-0 Isopropyl Alcohol

PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 491 mg/m ³ , 200 ppm BEI, A4

CAS: 7664-41-7 Ammonia

PEL (USA)	Long-term value: 35 mg/m ³ , 50 ppm
REL (USA)	Short-term value: 27 mg/m ³ , 35 ppm Long-term value: 18 mg/m ³ , 25 ppm
TLV (USA)	Short-term value: 24 mg/m ³ , 35 ppm Long-term value: 17 mg/m ³ , 25 ppm

· Ingredients with biological limit values:

CAS: 75-09-2 Methylene chloride

BEI (USA)	0.3 mg/L Medium: urine Time: end of shift Parameter: Dichloromethane (semi-quantitative)
-----------	---

CAS: 67-56-1 Methanol

BEI (USA)	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----------	---

CAS: 1330-20-7 Dimethylbenzene

BEI (USA)	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

CAS: 67-63-0 Isopropyl Alcohol

BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----------	---

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.

(Contd. on page 7)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

(Contd. of page 6)

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	40 °C

· Flash point: < 23 °C

· Flammability Highly flammable.

· Auto-ignition temperature: 455 °C

· Decomposition temperature: Not determined.

(Contd. on page 8)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

(Contd. of page 7)

· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	13 Vol %
Upper:	22 Vol %
· Vapour pressure at 20 °C:	453 hPa
· Density at 20 °C:	1.19 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	97.0 %
VOC (EC)	97.05 %
Solids content:	2.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· LD/LC50 values relevant for classification:		
CAS: 75-09-2 Methylene chloride		
Oral	LD50	1,600 mg/kg (rat)

(Contd. on page 9)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

(Contd. of page 8)

Inhalative	LC50/4 h	88 mg/l (rat)
CAS: 67-56-1 Methanol		
Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)
CAS: 1330-20-7 Dimethylbenzene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
CAS: 67-63-0 Isopropyl Alcohol		
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)
CAS: 7664-41-7 Ammonia		
Oral	LD50	350 mg/kg (rat)
Inhalative	LC50/4 h	2,000 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

PH

(Contd. on page 10)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026


Trade name: GI PAINT AND VARNISH REMOVER

(Contd. of page 9)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

* **14 Transport information**

· UN-Number · ADR, IMDG, IATA	UNI263
· UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
· Transport hazard class(es) · ADR, IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADR, IMDG, IATA	I
· Environmental hazards:	Product contains environmentally hazardous substances: Ammonia
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number:	Warning: Flammable liquids. 33 F-E,S-E
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	500 ml Code: E3 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 300 ml
· Transport category	1

(Contd. on page 11)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

(Contd. of page 10)

- **IMDG**
- **Limited quantities (LQ)** 500 ml
- **Excepted quantities (EQ)** Code: E3
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 300 ml
- **UN "Model Regulation":** UN 1263 PAINT, 3, I

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**

All ingredients are listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

H3 STOT SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **National regulations:**

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 127087-87-0 α -(4-nonylphenyl)- ω -hydroxy poly(oxy-1,2-ethanediyl), branched

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H221 Flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H303 May be harmful if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.

(Contd. on page 12)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

(Contd. of page 11)

- H332 Harmful if inhaled.
- H333 May be harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H370 Causes damage to organs.
- H371 May cause damage to organs.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R11 Highly flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- R23 Toxic by inhalation.
- R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
- R34 Causes burns.
- R36 Irritating to eyes.
- R38 Irritating to skin.
- R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
- R40 Limited evidence of a carcinogenic effect.
- R50 Very toxic to aquatic organisms.
- R67 Vapours may cause drowsiness and dizziness.

· **Department issuing SDS:** Product safety department

· **Contact:** Mr. Ong

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 2: Flammable gases – Category 2

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 5: Acute toxicity – Category 5

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 1B: Carcinogenicity – Category 1B

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

(Contd. on page 13)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: GI PAINT AND VARNISH REMOVER

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
· *** Data compared to the previous version altered.**

(Contd. of page 12)

PH