



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

1 Identification

- **Product identifier**
- **Trade name:** MAYON ACRYLIC THINNER
- **Article number:** CWCSBA-00050
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Company Name : Treasure Island Chemical Corp.
Company Address: Sitio Pilit Cabancalan, 6014 City of Mandaue, Cebu Philippines
Email Address: ddo@treasureisland.com.ph
Contact No.: +63 32 346 49 54-55
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**



GHS02 flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



GHS06 skull and crossbones

Acute Tox. 3

H331 Toxic if inhaled.



GHS08 health hazard

Muta. 1B

H340 May cause genetic defects.

Carc. 1B

H350 May cause cancer.

Repr. 2

H361 Suspected of damaging fertility or the unborn child.

STOT SE 1

H370 Causes damage to the central nervous system and the visual organs.

STOT RE 2

H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1

H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4

H302 Harmful if swallowed.

Skin Irrit. 2

H315 Causes skin irritation.

Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

(Contd. on page 2)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 1)

STOT SE 3
CWCSBA-00050

H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



T; Toxic

R45-46-23/24/25-39/23/24/25: May cause cancer. May cause heritable genetic damage. Toxic by inhalation, in contact with skin and if swallowed. Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.



Xn; Harmful

R48/20-63-65: Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.



Xi; Irritant

R38: Irritating to skin.



F; Highly flammable

R11: Highly flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:



T Toxic

F Highly flammable

Hazard-determining components of labelling:

Methanol
Methylbenzene
Naphtha (petroleum), hydrotreated light

Risk phrases:

45 May cause cancer.
46 May cause heritable genetic damage.
11 Highly flammable.
23/24/25 Also toxic by inhalation, in contact with skin and if swallowed.
38 Irritating to skin.
39/23/24/25 Also toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

(Contd. on page 3)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 2)

- 48/20 Also harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 63 Possible risk of harm to the unborn child.
- 65 Harmful: may cause lung damage if swallowed.

Safety phrases:

- 53 Avoid exposure - obtain special instructions before use.
- 1/2 Keep locked up and out of the reach of children.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 63 In case of accident by inhalation: remove casualty to fresh air and keep at rest.

Other hazards

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition / information on ingredients

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 67-56-1	<p>Methanol</p> <p> T R23/24/25-39/23/24/25</p> <p> F R11</p> <p> Flam. Liq. 2, H225</p> <p> Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331</p> <p> STOT SE 1, H370</p> <p>Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %</p>	
CAS: 108-88-3	<p>Methylbenzene</p> <p> Xn R48/20-63-65</p> <p> Xi R38</p> <p> F R11</p> <p>R67</p> <p>Repr. Cat. 3</p> <p> Flam. Liq. 2, H225</p> <p> Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304</p> <p> Skin Irrit. 2, H315; STOT SE 3, H336</p> <p>Acute Tox. 5, H303</p>	
CAS: 64742-49-0	<p>Naphtha (petroleum), hydrotreated light</p> <p> T Carc. Cat. 2, Muta. Cat. 2 R45-46</p> <p> Xn R65</p> <p> Flam. Liq. 2, H225</p> <p> Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304</p> <p> Aquatic Chronic 2, H411</p> <p> Skin Irrit. 2, H315; STOT SE 3, H336</p> <p>Aquatic Acute 2, H401</p>	

(Contd. on page 4)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 3)

CAS: 123-86-4	<p>Butyl Ethanoate</p> <p> Xn R22 Xi R36/38 F+ R12 R67</p> <p> Flam. Liq. 3, H226 Acute Tox. 3, H301 Skin Irrit. 2, H315; Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H336</p>	
CAS: 67-64-1	<p>propanone</p> <p> Xi R36 F R11 R66-67</p> <p> Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336</p>	
CAS: 78-93-3	<p>Methyl Ethyl Ketone</p> <p> Xi R36 F R11 R66-67</p> <p> Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H303; Acute Tox. 5, H313</p>	
CAS: 111-76-2	<p>BUTYL CELLOSOLVE</p> <p> Xn R20/21/22 Xi R36/38</p> <p> Flam. Liq. 3, H226 Acute Tox. 3, H331 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319</p>	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 5)



Safety Data Sheet according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 4)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.

(Contd. on page 6)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 5)

- Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 67-56-1 Methanol

PEL (USA)	Long-term value: 260 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV (USA)	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

CAS: 108-88-3 Methylbenzene

PEL (USA)	Long-term value: 200 ppm Ceiling limit: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, OTO, A4

CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light

TLV (USA)	Long-term value: 100 ppm Skin, A3
-----------	--------------------------------------

CAS: 123-86-4 Butyl Ethanoate

PEL (USA)	Long-term value: 710 mg/m ³ , 150 ppm
REL (USA)	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV (USA)	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

CAS: 67-64-1 propanone

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm A4, BEI

CAS: 78-93-3 Methyl Ethyl Ketone

PEL (USA)	Long-term value: 590 mg/m ³ , 200 ppm
-----------	--

(Contd. on page 7)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 6)

REL (USA) Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm

TLV (USA) Short-term value: 150 ppm
Long-term value: 75 ppm
BEI, Skin

CAS: 111-76-2 BUTYL CELLOSOLVE

PEL (USA) Long-term value: 240 mg/m³, 50 ppm
Skin

REL (USA) Long-term value: 24 mg/m³, 5 ppm
Skin

TLV (USA) Long-term value: 97 mg/m³, 20 ppm
BEI, A3

Ingredients with biological limit values:

CAS: 67-56-1 Methanol

BEI (USA) 15 mg/L
Medium: urine
Time: end of shift
Parameter: Methanol (background, nonspecific)

CAS: 108-88-3 Methylbenzene

BEI (USA) 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

CAS: 67-64-1 propanone

BEI (USA) 25 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

CAS: 78-93-3 Methyl Ethyl Ketone

BEI (USA) 2 mg/L
Medium: urine
Time: end of shift
Parameter: Methyl ethyl ketone (nonspecific)

(Contd. on page 8)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 7)

CAS: 111-76-2 BUTYL CELLOSOLVE

BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
-----------	--

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

(Contd. on page 9)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: **MAYON ACRYLIC THINNER**

(Contd. of page 8)

· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	64.7 °C
· Flash point:	< 0 °C
· Flammability	Highly flammable.
· Auto-ignition temperature:	215 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	44 Vol %
· Vapour pressure at 20 °C:	128 hPa
· Density at 20 °C:	0.8 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	100.00 %
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 10)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 9)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

CAS: 67-56-1 Methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

CAS: 108-88-3 Methylbenzene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

CAS: 67-64-1 propanone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

CAS: 78-93-3 Methyl Ethyl Ketone

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)

CAS: 111-76-2 BUTYL CELLOSOLVE

Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Toxic
Irritant
Carcinogenic.
The product can cause inheritable damage.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 11)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER


(Contd. of page 10)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · ADR, IMDG, IATA	UNI263
· UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
· Transport hazard class(es) · ADR, IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADR, IMDG, IATA	I
· Environmental hazards: · Marine pollutant:	Yes
· Special precautions for user · Hazard identification number (Kemler code):	Warning: Flammable liquids. 33

(Contd. on page 12)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 11)

· EMS Number:	<i>F-E,S-E</i>
· Transport in bulk according to Annex II of Marpol and the IBC Code	<i>Not applicable.</i>
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	<i>500 ml</i>
· Excepted quantities (EQ)	<i>Code: E3</i>
	<i>Maximum net quantity per inner packaging: 30 ml</i>
	<i>Maximum net quantity per outer packaging: 300 ml</i>
· Transport category	<i>1</i>
· IMDG	
· Limited quantities (LQ)	<i>500 ml</i>
· Excepted quantities (EQ)	<i>Code: E3</i>
	<i>Maximum net quantity per inner packaging: 30 ml</i>
	<i>Maximum net quantity per outer packaging: 300 ml</i>
· UN "Model Regulation":	<i>UN 1263 PAINT, 3, I</i>

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**

All ingredients are listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** *None of the ingredients is listed.*

· **Seveso category**

H2 ACUTE TOXIC

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** *50 t*

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** *200 t*

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

(Contd. on page 13)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 12)

- H302 Harmful if swallowed.
 - H303 May be harmful if swallowed.
 - H304 May be fatal if swallowed and enters airways.
 - H311 Toxic in contact with skin.
 - H312 Harmful in contact with skin.
 - H313 May be harmful in contact with skin.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H331 Toxic if inhaled.
 - H336 May cause drowsiness or dizziness.
 - H340 May cause genetic defects.
 - H350 May cause cancer.
 - H361 Suspected of damaging fertility or the unborn child.
 - H370 Causes damage to organs.
 - H371 May cause damage to organs.
 - H373 May cause damage to organs through prolonged or repeated exposure.
 - H401 Toxic to aquatic life.
 - H411 Toxic to aquatic life with long lasting effects.
-
- R11 Highly flammable.
 - R12 Extremely flammable.
 - R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
 - R22 Harmful if swallowed.
 - R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
 - R36 Irritating to eyes.
 - R36/38 Irritating to eyes and skin.
 - R38 Irritating to skin.
 - R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
 - R45 May cause cancer.
 - R46 May cause heritable genetic damage.
 - R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 - R63 Possible risk of harm to the unborn child.
 - R65 Harmful: may cause lung damage if swallowed.
 - R66 Repeated exposure may cause skin dryness or cracking.
 - R67 Vapours may cause drowsiness and dizziness.

· **Department issuing SDS:** Product safety department

· **Contact:** Mr. Ong

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent

(Contd. on page 14)



Safety Data Sheet
according to GHS

Printing date 02.03.2026

Revision: 02.03.2026

Trade name: MAYON ACRYLIC THINNER

(Contd. of page 13)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 5: Acute toxicity – Category 5
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1B: Carcinogenicity – Category 1B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
*** Data compared to the previous version altered.**

PH