

GI LACQUER FLO

DESCRIPTION:

GI LACQUER FLO is a blend of special solvents which helps the lacquer retard the drying time to achieve good flow and levelling specially in humid condition.

USE:

- As an additive for Lacquer-based Paint to ensure good flow or levelling.
- As an additive for Sanding Sealer and Clear Gloss Lacquer.
- Prevent moisture blushing
- Enhance the gloss of Lacquer-based Paint

COLOR/APPEARANCE:

Water-white, clear liquid

RECOMMENDED MIXING RATIO:

Mixing ¼ liter of GI Lacquer Flo to a gallon of ready to spray lacquer will give best result under humid to cold weather condition.

PACKAGING:

350cc bottle; 1L, 3.75L and 18L tin can
200L drum

SHELF LIFE:

2 years in unopened container

NOTE: High humidity might reduce the shelf-life of product.

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

LABEL ELEMENTS :



Warning: Flammable liquid and vapour. Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes skin and serious eye irritation.

Contains: Normal Butyl Cellulose, Dimethylbenzene

Precaution: Keep out of the reach of children. Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. Dispose of this material and its container to hazardous or special waste collection point.



The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests; neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

Rev. 0



ISO 9001 CERTIFIED

Treasure Island
CHEMICAL CORPORATION



HEAD OFFICE

CEBU
No. 2 3rd Avenue,
S. Osmeña Boulevard,
North Reclamation Area,
Cebu City, Philippines

Tel: (032) 232-0513 to 17
Fax: (032) 232-0518

LUZON

CAVITE
1530 ME,
Barangay Toalong
Kawit, Cavite

Tel: (046) 434-2229

VISAYAS

CEBU SHOWROOM
A.S Fortuna Street,
Mandaue City

Tel: (032) 345-2139
Fax: (032) 345-2130

MINDANAO

DAVAO
No.8 NR
El Rio St. Subdivision
Bacaca Road, Davao City

Tel: (082) 224-3409
Fax: (082) 222-8476

EMAIL

sales@islandpaints.com

WEBSITE

www.islandpaints.com